



GRAS VAN DE BUREN



Technical specification | Fresno

Type	: tufted non filled synthetic grass carpet	
Yarn material	: PE monofilament straight & PP monofilament curled	
Yarn type	: 14.400/8/8 dTex + 6.600/12: combination of V-shape non directional, C-shape and oval shape texturized	
Yarn quality	: environmental friendly, UV stabilized, UV stability meets DIN 53387 standard : free of lead and cadmium	
Colour fastness	: xenon test: blue scale > 7, grey-scale > 4	
Primary backing	: 100% PP Thiobac ® with fleece, black, UV stabilized : weight 155 gr/m ²	
Secondary backing	: black latex compound with a base of styrene-butadiene (SBR), with drainage holes : weight 850 gr/m ²	
Tuft gauge	: 5/8"	
Pile height	: 40mm	(+/-10%)
Stitches per 10cm	: 11.5	(+/-10%)
Stitches per m²	: 7.250	(+/-10%)
Face weight	: 1.400 gr/m ²	(+/-10%)
Total weight	: 2.405 gr/m ²	(+/-10%)
Roll width	: 400cm + 200cm	(+/- 2cm)
Roll length	: 25.20 m ¹	(+/- 20cm)
	: roll length may vary	
Water permeability	: 60 liter/min/m ²	
Fire retardant classification	: Cfl-S1 (EN ISO 11925-2: sand filled ca. 5mm) : Efl-S1 (EN ISO 11925-2; non filled)	
Batch information	: before installation please make sure the batch numbers (AVL-....) are equal	
Shrinkage	: shrinkage can appear due to high temperatures. Make sure the carpet can relax before cutting	
Infill recommendation	: non infill (optional 5kg/m ²)	

Het gras van de buren is altijd groener!
www.grasvdburen.nl